


CELL CHARACTERISTICS

Capacity	Nominal	3,400 mAh 12.24 Wh
Cell Voltage	Nominal Charge Discharge	3.6 V 4.2 V 2.5 V
Continuous Charge Current	Standard Fast Charge	1.7 A 3.4 A
Charge Time	Standard Fast Charge	180 min 90 min
Continuous Discharge Current	Maximum	10 A
Internal Resistance	AC (1 KHz)	≤35 mΩ
Operating Temperature	Charge Discharge	0°C to 45°C -20°C to 60°C
Energy Density	Volumetric Gravimetric	762 Wh/L 263 Wh/kg

PHYSICAL CHARACTERISTICS




Shape	Cylindrical
Can	Steel
Diameter	65.3 mm (Max)
Height	18.6 mm (Max)
Weight	50 g (Max)




The information shown on this document is for descriptive purpose only. This document is not intended to make or imply any performance guarantee or a product warranty.

All specifications and characteristics shown herein are for REFERENCE ONLY, please check the latest version of the product specification for guidance. All specifications and characteristics shown herein are subject to change without prior notice and should be verified with a Tenpower representative or the nearest Tenpower recognized agent before placing an order.


CHARGE RATE CHARACTERISTICS




DISCHARGE RATE CHARACTERISTICS



DISCHARGE TEMPERATURE CHARACTERISTICS




CYCLE LIFE CHARACTERISTICS



电芯特性

容量	标称	3,400 mAh 12.24 Wh
电压	标称 充电 放电	3.6 V 4.2 V 2.5 V
充电电流	标准 最大	1.7 A 3.4 A
充电时间	标准 快充	180 min 90 min
持续放电电流	最大	10 A
内阻	AC (1 KHz)	≤35 mΩ
工作温度	充电 放电	0°C to 45°C -20°C to 60°C
能量密度	体积 重量	762 Wh/L 263 Wh/kg

物理特性




外形	圆柱
外壳	钢
直径	65.3 mm (最大)
高度	18.6 mm (最大)
重量	50 g (最大)




本文档中显示的信息仅用于描述目的。本文档无意提供或暗示任何性能保证或产品保修。

此处显示的所有规格和特性如有变更，恕不另行通知，在下订单之前，应与天鹏电源授权代表或最近的天鹏电源认可之代理商进行核实。


充电倍率特性



放电倍率特性



放电温度特性



循环特性

